

Package ‘BBMBC’

October 7, 2026

Title Beta-Binomial Models for Vaccine-Specific Memory B Cell
Frequency and Power Calculations

Version 0.1.0

Description Provides tools to model overdispersed vaccine-specific memory B cell frequencies using Beta-Binomial generalized linear models, specifically designed for analyzing vaccine-induced cellular immune responses. Includes method-of-moments dispersion estimation, likelihood ratio testing across experimental arms, and Monte Carlo simulation frameworks to calculate statistical power and Type I error rates. The methodologies are directly motivated by the analysis of immunology data in 'Vaccination with mRNA-encoded membrane-anchored HIV envelope trimers elicited tier 2 neutralizing antibodies in a phase 1 clinical trial' (Parks et al. 2025) <[doi:10.1126/scitranslmed.ady6831](https://doi.org/10.1126/scitranslmed.ady6831)>.

Encoding UTF-8

Depends R (>= 4.1.0)

Imports doParallel, foreach, glmmTMB, parallel, stats, utils

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

License MIT + file LICENSE

NeedsCompilation no

Author Andrew Shin [aut, cre]

Maintainer Andrew Shin <ashin2@uw.edu>

Repository CRAN

Date/Publication 2026-10-07 08:10:20 UTC

Contents

calc_power_bb	2
calc_rho_mom	3
calc_t1_bb	4
test_diff_bb	5

Index[7](#)

calc_power_bb	<i>Calculate Statistical Power for Beta-Binomial Models (Parallelized)</i>
---------------	--

Description

Simulates overdispersed cell frequency data under the alternative hypothesis to estimate the statistical power of a Beta-Binomial generalized linear model.

Usage

```
calc_power_bb(
  n_0 = 20,
  n_1 = 20,
  p_base = 0.005,
  fold_change = 2,
  rho_0 = 0.006,
  rho_1 = 0.006,
  alpha = 0.05,
  min_cells = 1e+05,
  max_cells = 1e+06,
  seed = 2025,
  n_sims = 1000,
  n_cores = min(2, max(1, parallel::detectCores() - 1))
)
```

Arguments

n_0	Integer. Biological replicates in control arm (default: 20).
n_1	Integer. Biological replicates in treatment arm (default: 20).
p_base	Numeric. Baseline proportion in control group (default: 0.005).
fold_change	Numeric. Ratio of treatment mean to control mean (default: 2.0).
rho_0	Numeric. Overdispersion for control group (default: 0.006).
rho_1	Numeric. Overdispersion for treatment group (default: 0.006).
alpha	Numeric. Significance threshold for likelihood ratio test (default: 0.05).
min_cells	Integer. Minimum total cells per sample (default: 1e5).
max_cells	Integer. Maximum total cells per sample (default: 1e6).
seed	Integer. Random seed for reproducibility (default: 2025).
n_sims	Integer. Number of simulations to run (default: 1000).
n_cores	Integer. Number of cores for parallel processing. Defaults to 2 (CRAN safe default).

Value

A list of class `power_result` containing the estimated statistical power, convergence metrics, and the input parameters used.

Examples

```
# Evaluate statistical power across a range of sample sizes
sample_sizes <- c(10, 15, 20, 25)
power_results <- numeric(length(sample_sizes))
names(power_results) <- paste0("N=", sample_sizes, "/arm")

for (i in seq_along(sample_sizes)) {
  n <- sample_sizes[i]

  # Run simulation for the current sample size
  # Note: n_sims = 100 is used here for demonstration speed.
  # For formal analysis, use n_sims = 1000 or higher.
  pwr_res <- calc_power_bb(
    n_0 = n, n_1 = n,
    p_base = 0.005,
    fold_change = 2.0,
    rho_0 = 0.006, rho_1 = 0.006,
    n_sims = 100,
    n_cores = 1
  )

  power_results[i] <- pwr_res$power
}

# Print the resulting power curve estimates
print(power_results)
```

calc_rho_mom

*Estimate Overdispersion (Rho) via Method of Moments***Description**

Calculates a rapid empirical estimate of the intra-class correlation (overdispersion parameter, ρ) for proportion data. This method of moments estimator uses the ratio of the sample variance of the proportions to the theoretical maximum variance of a true binomial distribution with the same mean.

Usage

```
calc_rho_mom(props, na.rm = TRUE)
```

Arguments

props	Numeric vector of observed proportions (must be between 0 and 1).
na.rm	Logical. Should missing values (including NaN) be removed before computation? (default: TRUE).

Value

A numeric value representing the estimated overdispersion parameter (ρ). Returns NA if the sample mean is exactly 0 or 1, as the denominator becomes 0.

Examples

```
# Simulate 100 proportions with a known mean of 0.2 and overdispersion of 0.05
set.seed(123)
p_base <- 0.2
rho_true <- 0.05
shape1 <- p_base * (1 - rho_true) / rho_true
shape2 <- (1 - p_base) * (1 - rho_true) / rho_true

sim_props <- stats::rbeta(100, shape1, shape2)

# Estimate rho empirically
estimated_rho <- calc_rho_mom(sim_props)
print(estimated_rho)
```

calc_t1_bb

Calculate Type I Error for Beta-Binomial Models

Description

Simulates immunology data under the null hypothesis of equal means (no biological difference in cell frequency) using parallel processing. Handles balanced/unbalanced sample sizes and dynamic overdispersion.

Usage

```
calc_t1_bb(
  n_0 = 20,
  n_1 = 20,
  p_base = 0.005,
  rho_0 = 0.006,
  rho_1 = 0.006,
  alpha = 0.05,
  min_cells = 1e+05,
  max_cells = 1e+06,
  seed = 2026,
  n_sims = 1000,
  n_cores = min(2, max(1, parallel::detectCores() - 1))
)
```

Arguments

n_0	Integer. The number of biological replicates in the control arm (default: 20).
n_1	Integer. The number of biological replicates in the treatment arm (default: 20).
p_base	Numeric. Baseline proportion of the target cell population for BOTH groups (default: 0.005).
rho_0	Numeric. Intra-class correlation (overdispersion) for the control group (default: 0.006).
rho_1	Numeric. Intra-class correlation (overdispersion) for the treatment group (default: 0.006).
alpha	Numeric. Significance threshold for the likelihood ratio test (default: 0.05).
min_cells	Integer. Minimum number of total cells analyzed per sample (default: 1e5).
max_cells	Integer. Maximum number of total cells analyzed per sample (default: 1e6).
seed	Integer. Random seed for reproducibility (default: 2026).
n_sims	Integer. The number of simulations to run (default: 1000).
n_cores	Integer. Number of cores to use for parallel processing. Defaults to 2 (CRAN safe default).

Value

A list of class `t1_error_result` containing the estimated Type I error rate, convergence metrics, and the input parameters.

Examples

```
# Run small simulation example
res <- calc_t1_bb(
  n_0 = 10, n_1 = 10,
  rho_0 = 0.006, rho_1 = 0.006,
  n_sims = 10,
  n_cores = 1
)
print(res$type_1_error_rate)
```

test_diff_bb

*Beta-Binomial Likelihood Ratio Test for Group Differences***Description**

Performs a Likelihood Ratio Test (LRT) using Beta-Binomial models to evaluate whether the underlying proportion of events differs significantly between two groups.

Usage

```
test_diff_bb(  
  data,  
  success_col,  
  total_col,  
  group_col,  
  unequal_dispersion = FALSE  
)
```

Arguments

data	A data frame containing the experimental data.
success_col	Character string specifying the column name for successes.
total_col	Character string specifying the column name for total trials.
group_col	Character string specifying the column name with group labels (must have 2 levels).
unequal_dispersion	Logical. If TRUE, models group-specific overdispersion. Default: FALSE.

Value

A list of class `bb_test_result` containing p-value, chi-square statistic, degrees of freedom, log-odds ratio, and its standard error.

Examples

```
set.seed(2025)  
trial_data <- data.frame(  
  arm = rep(c("Control", "Vaccine"), each = 15),  
  total_bcells = as.integer(stats::runif(30, 100000, 500000))  
)  
trial_data$target_cells <- ifelse(  
  trial_data$arm == "Control",  
  stats::rbinom(15, trial_data$total_bcells, stats::rbeta(15, 5, 995)),  
  stats::rbinom(15, trial_data$total_bcells, stats::rbeta(15, 10, 990))  
)  
  
result <- test_diff_bb(  
  data = trial_data,  
  success_col = "target_cells",  
  total_col = "total_bcells",  
  group_col = "arm",  
  unequal_dispersion = FALSE  
)  
print(result$p_value)
```

Index

`calc_power_bb`, [2](#)

`calc_rho_mom`, [3](#)

`calc_t1_bb`, [4](#)

`test_diff_bb`, [5](#)