

Package ‘mongolstats’

January 26, 2026

Type Package

Title Mongolian 'NSO' 'PXWeb' Data and Boundaries (Tidy Client)

Version 0.1.1

Description A 'tidyverse'-friendly client for the National Statistics Office of Mongolia 'PXWeb' API <<https://data.1212.mn/>> with helpers to discover tables, variables, and fetch statistical data. Also includes utilities to retrieve Mongolia administrative boundaries (ADM0-ADM2) as 'sf' objects from open sources for mapping and spatial analysis.

Depends R (>= 4.1.0)

Imports htr2, jsonlite, tibble, dplyr, purrr, stringr, sf, memoise, cachem, rappdirs, stringi, stringdist, curl

Suggests testthat (>= 3.0.0), knitr, rmarkdown, pkgdown, roxygen2, lifecycle, pxweb, remotes, httptest2, covr, lintr, styler, future, future.apply, cli, ggplot2, scales, forcats, tidyr, lubridate

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.3

Config/testthat/edition 3

URL <https://temuulene.github.io/mongolstats/>,
<https://data.1212.mn/pxweb/>

BugReports <https://github.com/temuulene/mongolstats/issues>

License MIT + file LICENSE

NeedsCompilation no

Author Temuulen Enebish [aut, cre, cph]

Maintainer Temuulen Enebish <temuulen@gmail.com>

Repository CRAN

Date/Publication 2026-01-26 07:50:02 UTC

Contents

as_px_query	2
mn_boundaries	3
mn_boundaries_normalize	4
mn_boundary_keys	4
mn_fuzzy_join_by_name	5
mn_join_by_name	6
nso_cache_clear	6
nso_cache_disable	7
nso_cache_enable	7
nso_cache_status	8
nso_data	8
nso_dims	9
nso_dim_values	10
nso_fetch	11
nso_itms	11
nso_itms_by_sector	12
nso_itms_detail	13
nso_itms_search	13
nso_offline_disable	14
nso_offline_enable	14
nso_options	15
nso_package	16
nso_period_seq	16
nso_query	17
nso_rebuild_px_index	18
nso_search	18
nso_sectors	19
nso_subsectors	20
nso_table_meta	20
nso_table_periods	21
Index	22

as_px_query	<i>Convert a query to a PXWeb body</i>
-------------	--

Description

Convert a query to a PXWeb body

Usage

```
as_px_query(x, lang = .px_lang())
```

Arguments

`x` An nso_query object.

`lang` PX language: "en" or "mn" (defaults to current option).

Value

A list suitable to send as JSON body to PXWeb.

Examples

```
q <- nso_query("DT_NS0_0300_001V2", list(Year = "2023"))
body <- as_px_query(q)
```

mn_boundaries	<i>Mongolia administrative boundaries (sf)</i>
---------------	--

Description

Downloads Mongolia boundaries for ADM0/ADM1/ADM2 from the GeoBoundaries API and returns an sf object. Results can be cached by the caller as needed.

Usage

```
mn_boundaries(level = c("ADM0", "ADM1", "ADM2"))
```

Arguments

`level` One of "ADM0", "ADM1", "ADM2".

Value

An sf object with polygons for the requested level.

Examples

```
# Get aimag (province) boundaries
aimags <- mn_boundaries("ADM1")
head(aimags)
```

`mn_boundaries_normalize`*Add normalized name columns to boundaries*

Description

Add normalized name columns to boundaries

Usage

```
mn_boundaries_normalize(g, name_col = "shapeName")
```

Arguments

`g` sf object from `mn_boundaries()`
`name_col` Column with English names (default 'shapeName').

Value

sf with `name_std` column added.

Examples

```
aimags <- mn_boundaries("ADM1")  
aimags <- mn_boundaries_normalize(aimags)  
head(aimags$name_std)
```

`mn_boundary_keys`*Boundary keys/crosswalk helper*

Description

Boundary keys/crosswalk helper

Usage

```
mn_boundary_keys(level = "ADM1")
```

Arguments

`level` Boundary level.

Value

tibble with key columns from GeoBoundaries and normalized names.

Examples

```
keys <- mn_boundary_keys("ADM1")
head(keys)
```

mn_fuzzy_join_by_name *Fuzzy join data to boundaries by name*

Description

Fuzzy join data to boundaries by name

Usage

```
mn_fuzzy_join_by_name(
  data,
  name_col,
  level = "ADM1",
  boundaries = NULL,
  max_distance = 2,
  method = c("osa", "lv", "jw", "dl")
)
```

Arguments

data	Data frame with a name column.
name_col	Column in data containing names.
level	Boundary level.
boundaries	Optional pre-fetched boundaries.
max_distance	Maximum string distance for a match (default 2).
method	Distance method passed to <code>stringdist::stringdist</code> .

Value

sf with best fuzzy matches joined.

Examples

```
# Join even with minor spelling differences
pop_data <- data.frame(aimag = c("Ulanbatar", "Darhan"), pop = c(1500000, 100000))
sf_joined <- mn_fuzzy_join_by_name(pop_data, "aimag", level = "ADM1")
```

mn_join_by_name	<i>Join data to boundaries by (normalized) names</i>
-----------------	--

Description

Join data to boundaries by (normalized) names

Usage

```
mn_join_by_name(data, name_col, level = "ADM1", boundaries = NULL)
```

Arguments

data	Data frame with a name column.
name_col	Column in data that contains names to join on.
level	Boundary level, passed to mn_boundaries() if boundaries not provided.
boundaries	Optional pre-fetched boundaries.

Value

sf with joined data.

Examples

```
pop_data <- data.frame(aimag = c("Ulaanbaatar", "Darkhan-Uul"), pop = c(1500000, 100000))
sf_joined <- mn_join_by_name(pop_data, "aimag", level = "ADM1")
```

nso_cache_clear	<i>Clear cached entries</i>
-----------------	-----------------------------

Description

Clear cached entries

Usage

```
nso_cache_clear()
```

Value

No return value, called for side effects.

Examples

```
nso_cache_clear()
```

nso_cache_disable	<i>Disable caching</i>
-------------------	------------------------

Description

Disable caching

Usage

```
nso_cache_disable()
```

Value

No return value, called for side effects.

Examples

```
nso_cache_disable()
```

nso_cache_enable	<i>Enable or configure caching</i>
------------------	------------------------------------

Description

Caches table lists and codebooks on disk to speed up repeated calls. Optionally set a time-to-live (TTL) for cache entries.

Usage

```
nso_cache_enable(dir = NULL, ttl = NULL)
```

Arguments

dir	Directory for cache; defaults to user cache dir.
ttl	Optional TTL in seconds for cached entries (applies to the disk cache). If NULL, entries persist until cleared.

Value

Cache directory path (invisibly).

Examples

```
# Enable caching in a temporary directory (for demo purposes)
cache_dir <- nso_cache_enable(dir = tempdir())

# Check status
nso_cache_status()

# Disable when done
nso_cache_disable()
```

nso_cache_status	Cache status
------------------	--------------

Description

Report current cache configuration and basic stats.

Usage

```
nso_cache_status()
```

Value

A list with enabled, dir, and has_cache.

Examples

```
nso_cache_status()
```

nso_data	Fetch statistical data for a table (PXWeb)
----------	--

Description

Fetch statistical data for a table (PXWeb)

Usage

```
nso_data(
  tbl_id,
  selections,
  labels = c("none", "en", "mn", "both"),
  value_name = getOption("mongolstats.value_name", "value"),
  include_raw = getOption("mongolstats.attach_raw", FALSE)
)
```

Arguments

tbl_id	Table identifier (e.g., "DT_NSO_0300_001V2").
selections	Named list mapping variable labels (e.g., Year, Sex) to desired codes or labels.
labels	Label handling: "none" (codes only), "en", "mn", or "both".
value_name	Name of the numeric value column in the result (default: "value").
include_raw	If TRUE, attach the raw PX payload as attribute px_raw.

Value

A tibble with one column per dimension and a numeric value column.

Table Structure Notes

Some NSO tables have unique dimension structures that affect how selections should be constructed:

- **Air Quality Monthly Tables** (e.g., DT_NSO_2400_015V1 to V6): These tables do not have a Year dimension. Instead, they use a running Month dimension with integer codes (e.g., "0" for the most recent month). Example: `selections = list(Month = as.character(0:11))` retrieves the last 12 months.

Examples

```
# Fetch population data
pop <- nso_data(
  tbl_id = "DT_NSO_0300_001V2",
  selections = list(Year = "2023")
)
head(pop)
```

nso_dims

List dimensions for a PXWeb table

Description

Returns one row per dimension with basic metadata.

Usage

```
nso_dims(tbl_id)
```

Arguments

tbl_id	Table identifier (e.g., "DT_NSO_0300_001V2").
--------	---

Value

A tibble with columns: dim (display name), code (dimension code), is_time (logical), and n_values (number of values for the dimension).

Examples

```
dims <- nso_dims("DT_NSO_0300_001V2")
dims
```

nso_dim_values	<i>List values for a table dimension</i>
----------------	--

Description

Returns codes and optional labels for a specific dimension.

Usage

```
nso_dim_values(tbl_id, dim, labels = c("code", "en", "mn", "both"))
```

Arguments

- tbl_id Table identifier (e.g., "DT_NSO_0300_001V2").
- dim Dimension name or code (case-insensitive; exact match preferred).
- labels One of "code", "en", "mn", or "both" to control returned label columns.

Value

A tibble with at least code; may include label_en and/or label_mn.

Examples

```
values <- nso_dim_values("DT_NSO_0300_001V2", "Year")
head(values)
```

nso_fetch	<i>Fetch a query and return a tibble</i>
-----------	--

Description

Executes an nso_query and returns a tidy tibble with one column per dimension and a numeric value column. Use labels to add _en/_mn columns for each dimension.

Usage

```
nso_fetch(
  x,
  labels = c("code", "en", "mn", "both"),
  value_name = getOption("mongolstats.value_name", "value"),
  include_raw = getOption("mongolstats.attach_raw", FALSE)
)
```

Arguments

x	An nso_query object.
labels	One of "code", "en", "mn", or "both" (mapped to internal API).
value_name	Name of the numeric value column in the result (default: "value").
include_raw	If TRUE, attach the raw PX payload as attribute px_raw.

Value

A tibble.

Examples

```
q <- nso_query("DT_NSO_0300_001V2", list(Year = "2023"))
data <- nso_fetch(q)
head(data)
```

nso_itms	<i>List available NSO tables (PXWeb)</i>
----------	--

Description

Returns a tibble of all available tables in the NSO PXWeb catalog.

Usage

```
nso_itms()

nso_tables()
```

Value

A tibble with columns: px_path, px_file, tbl_id, tbl_eng_nm, tbl_nm, strt_prd, end_prd, list_id.

Examples

```
# List all available tables
tables <- nso_itms()
head(tables)
```

nso_itms_by_sector	<i>List tables under a sector or sub-sector (PXWeb path)</i>
--------------------	--

Description

List tables under a sector or sub-sector (PXWeb path)

Usage

```
nso_itms_by_sector(list_id)
```

Arguments

list_id Path string from nso_sectors()/nso_subsectors() id.

Value

A tibble of tables matching the specified sector path.

Examples

```
sectors <- nso_sectors()
tables <- nso_itms_by_sector(sectors$id[1])
```

nso_itms_detail	<i>Get variable codes for a table (PXWeb)</i>
-----------------	---

Description

Get variable codes for a table (PXWeb)

Usage

```
nso_itms_detail(tbl_id)
```

```
nso_variables(tbl_id)
```

Arguments

tbl_id	Table identifier (e.g., "DT_NSO_0300_001V2").
--------	---

Value

A tibble with variable metadata.

Examples

```
vars <- nso_itms_detail("DT_NSO_0300_001V2")
vars
```

nso_itms_search	<i>Search tables by keyword (PXWeb)</i>
-----------------	---

Description

Search tables by keyword (PXWeb)

Usage

```
nso_itms_search(query, fields = c("tbl_eng_nm", "tbl_nm"))
```

Arguments

query	A single keyword string to search for (case-insensitive).
fields	Character vector of column names to search within (defaults to English and Mongolian titles).

Value

A tibble of matching tables.

Examples

```
# Search for population tables
nso_itms_search("population")
```

nso_offline_disable	<i>Disable offline mode</i>
---------------------	-----------------------------

Description

Disable offline mode

Usage

```
nso_offline_disable()
```

Value

Invisibly, TRUE.

Examples

```
nso_offline_disable()
```

nso_offline_enable	<i>Enable offline mode</i>
--------------------	----------------------------

Description

When enabled, HTTP requests are prevented and functions that require the network will raise a clear offline error. Cached metadata can still be used if already available via nso_cache_enable().

Usage

```
nso_offline_enable()
```

Value

Invisibly, TRUE.

Examples

```
# Enable offline mode
nso_offline_enable()

# Check the option was set
getOption("mongolstats.offline")

# Disable to restore normal operation
nso_offline_disable()
```

nso_options	<i>Set or get mongolstats options</i>
-------------	---------------------------------------

Description

Convenience wrapper around `base::options()` for mongolstats.

Usage

```
nso_options(...)
```

Arguments

... Named options to set. If empty, returns a named list of current mongolstats options.

Value

Invisibly, the previous values of the options changed, or a list of current values when called with no arguments.

Examples

```
# Get all current mongolstats options
nso_options()

# Set an option (save old value for restoration)
old <- nso_options(mongolstats.default_labels = "en")

# Restore original value
options(old)
```

nso_package

Fetch multiple tables and bind (PXWeb)

Description

Fetch multiple tables and bind (PXWeb)

Usage

```
nso_package(
  requests,
  labels = c("none", "en", "mn", "both"),
  parallel = getOption("mongolstats.parallel", FALSE),
  value_name = getOption("mongolstats.value_name", "value")
)
```

Arguments

requests	A list of records, each with tbl_id and selections (named list)
labels	Label handling as in nso_data()
parallel	If TRUE, use future.apply to fetch tables in parallel.
value_name	Name of the numeric value column in the result (default: "value").

Value

A tibble combining data from all requested tables, with a tbl_id column identifying the source table.

Examples

```
reqs <- list(
  list(tbl_id = "DT_NSO_0300_001V2", selections = list(Year = "2023"))
)
combined <- nso_package(reqs)
```

nso_period_seq

Create period codes

Description

Utilities to construct NSO period codes and sequences. For monthly data, use YYYYMM; for yearly, use YYYY.

Usage

```
nso_period_seq(start, end, by = c("Y", "M"))
```

Arguments

start, end Start and end periods as character (YYYY or YYYYMM).
by 'Y' for yearly or 'M' for monthly.

Value

Character vector of period codes.

Examples

```
# Generate yearly sequence
nso_period_seq("2020", "2024", by = "Y")

# Generate monthly sequence
nso_period_seq("202401", "202406", by = "M")
```

nso_query

Create a PXWeb query object

Description

Builds a lightweight query object that records a table id and selections. Use [nso_fetch\(\)](#) to execute it, or [as_px_query\(\)](#) to inspect the underlying PXWeb body.

Usage

```
nso_query(tbl_id, selections = list())
```

Arguments

tbl_id Table identifier, e.g. "DT_NSO_0300_001V2".
selections Named list mapping dimension labels (e.g., Year, Sex) to desired codes or labels.

Value

An object of class nso_query.

Examples

```
# Create a query object (does not require network)
q <- nso_query("DT_NSO_0300_001V2", list(Year = "2023", Sex = "Total"))
print(q)
```

nso_rebuild_px_index	<i>Rebuild PXWeb index and optionally write to a file</i>
----------------------	---

Description

Crawls the PXWeb API to rebuild the table index. If path is provided, the index is written to that file; otherwise only the in-memory index is refreshed.

Usage

```
nso_rebuild_px_index(path = NULL, write = !is.null(path))
```

Arguments

path	Output path for JSON. If NULL (default), no file is written. For package development, use "inst/extdata/px_index.json".
write	Whether to write JSON to path. Defaults to TRUE if path is provided, FALSE otherwise.

Value

A tibble containing the rebuilt table index.

Examples

```
# Rebuild in-memory index only (takes time to crawl API)

idx <- nso_rebuild_px_index()
head(idx)
```

nso_search	<i>Search NSO tables</i>
------------	--------------------------

Description

Search NSO tables

Usage

```
nso_search(query, sector = NULL, fields = c("tbl_eng_nm", "tbl_nm"))
```

Arguments

query	Search string (regex, case-insensitive).
sector	Optional sector/subsector list_id to filter results.
fields	Character vector of fields to search within.

Value

Tibble of matching tables.

Examples

```
nso_search("population")
```

nso_sectors	<i>List top-level categories (PXWeb NSO root)</i>
-------------	---

Description

List top-level categories (PXWeb NSO root)

Usage

```
nso_sectors()
```

Value

tibble with id, type, text

Examples

```
sectors <- nso_sectors()
head(sectors)
```

nso_subsectors	<i>List children for a given path (PXWeb)</i>
----------------	---

Description

List children for a given path (PXWeb)

Usage

```
nso_subsectors(subid)
```

Arguments

subid	Path id from nso_sectors()/nso_subsectors() (e.g., 'Population, household' or 'Population, household/1_Population, household')
-------	--

Value

A tibble with columns: id, type, text.

Examples

```
sectors <- nso_sectors()
nso_subsectors(sectors$id[1])
```

nso_table_meta	<i>Table metadata as per-dimension codebooks</i>
----------------	--

Description

Returns a tibble with one row per dimension and a codes list-column, where each element is a tibble of codes and labels (code, label_en, label_mn). Useful for manual query assembly and for inspecting available categories per dimension.

Usage

```
nso_table_meta(tbl_id)
```

Arguments

tbl_id	Table identifier (e.g., "DT_NSO_0300_001V2").
--------	---

Value

A tibble with columns: dim (display name), code (dimension code), is_time (logical), n_values (integer), and codes (list of tibbles).

Examples

```
meta <- nso_table_meta("DT_NSO_0300_001V2")
meta
```

nso_table_periods	<i>Get valid periods for a table (PXWeb)</i>
-------------------	--

Description

Get valid periods for a table (PXWeb)

Usage

```
nso_table_periods(tbl_id)
```

Arguments

tbl_id	Table identifier.
--------	-------------------

Value

Character vector of period labels (e.g., years)

Examples

```
periods <- nso_table_periods("DT_NSO_0300_001V2")
head(periods)
```

Index

`as_px_query`, [2](#)
`as_px_query()`, [17](#)

`base::options()`, [15](#)

`mn_boundaries`, [3](#)
`mn_boundaries_normalize`, [4](#)
`mn_boundary_keys`, [4](#)
`mn_fuzzy_join_by_name`, [5](#)
`mn_join_by_name`, [6](#)

`nso_cache_clear`, [6](#)
`nso_cache_disable`, [7](#)
`nso_cache_enable`, [7](#)
`nso_cache_status`, [8](#)
`nso_data`, [8](#)
`nso_dim_values`, [10](#)
`nso_dims`, [9](#)
`nso_fetch`, [11](#)
`nso_fetch()`, [17](#)
`nso_itms`, [11](#)
`nso_itms_by_sector`, [12](#)
`nso_itms_detail`, [13](#)
`nso_itms_search`, [13](#)
`nso_offline_disable`, [14](#)
`nso_offline_enable`, [14](#)
`nso_options`, [15](#)
`nso_package`, [16](#)
`nso_period_seq`, [16](#)
`nso_query`, [17](#)
`nso_rebuild_px_index`, [18](#)
`nso_search`, [18](#)
`nso_sectors`, [19](#)
`nso_subsectors`, [20](#)
`nso_table_meta`, [20](#)
`nso_table_periods`, [21](#)
`nso_tables(nso_itms)`, [11](#)
`nso_variables(nso_itms_detail)`, [13](#)