

Package ‘nose’

October 6, 2025

Type Package

Title Classification of Sparseness in 2-by-2 Categorical Data

Version 1.0.5

Date 2025-09-29

Maintainer Subbiah M <sisufive@gmail.com>

Description Provides functions for classifying sparseness in 2 x 2 categorical data where one or more cells have zero counts. The classification uses three widely applied summary measures: Risk Difference (RD), Relative Risk (RR), and Odds Ratio (OR). Helps in selecting suitable continuity corrections for zero cells in multi-centre or meta-analysis studies. Also supports sensitivity analysis and can detect phenomena such as Simpson's paradox. The methodology is based on Subbiah and Srinivasan (2008) <[doi:10.1016/j.spl.2008.06.023](https://doi.org/10.1016/j.spl.2008.06.023)>.

License GPL-2

Encoding UTF-8

RoxygenNote 7.3.1

NeedsCompilation no

Author Subbiah M [aut, cre]

Repository CRAN

Date/Publication 2025-10-06 05:40:02 UTC

Contents

nose.or	2
nose.rd	3
nose.rr	4

Index	5
--------------	----------

`nose.or`*Classify Sparseness in 2x2 Tables using Odds Ratio*

Description

Classifies sparseness in 2x2 categorical tables where one or more cells are zero. The classification uses widely applied summary measures and a continuity correction to determine whether a table exhibits mild, moderate, or severe sparseness.

Usage

```
nose.or(nos, cc)
```

Arguments

<code>nos</code>	A numeric matrix or data.frame with 4 columns representing counts in a 2x2 table: a (top-left), b (top-right), c (bottom-left), d (bottom-right). Each row corresponds to a separate 2x2 table.
<code>cc</code>	Continuity correction factor (numeric, e.g., 0.3)

Value

A matrix combining the input counts with an extra column indicating the sparseness classification for each table.

Examples

```
# Simple example: one 2x2 table with a zero cell
xx <- matrix(c(0, 3, 2, 5), nrow = 1, byrow = TRUE)
nose.or(xx, cc = 0.3)

# Multiple tables example: each row is a separate 2x2 table
tables <- matrix(c(
  0, 3, 2, 5,
  2, 0, 1, 4,
  0, 0, 2, 3
), nrow = 3, byrow = TRUE)
nose.or(tables, cc = 0.3)
```

`nose.rd`*Classify Sparseness in 2x2 Tables using Risk Difference*

Description

Classifies sparseness in 2x2 categorical tables where one or more cells are zero. The classification uses widely applied summary measures and a continuity correction to determine whether a table exhibits mild, moderate, or severe sparseness.

Usage

```
nose.rd(nos, cc)
```

Arguments

<code>nos</code>	A numeric matrix or data.frame with 4 columns representing counts in a 2x2 table: a (top-left), b (top-right), c (bottom-left), d (bottom-right). Each row corresponds to a separate 2x2 table.
<code>cc</code>	Continuity correction factor (numeric, e.g., 0.3)

Value

A matrix combining the input counts with an extra column indicating the sparseness classification for each table.

Examples

```
# Simple example: one 2x2 table with a zero cell
xx <- matrix(c(0, 3, 2, 5), nrow = 1, byrow = TRUE)
nose.rd(xx, cc = 0.3)

# Multiple tables example: each row is a separate 2x2 table
tables <- matrix(c(
  0, 3, 2, 5,
  2, 0, 1, 4,
  0, 0, 2, 3
), nrow = 3, byrow = TRUE)
nose.rd(tables, cc = 0.3)
```

`nose.rr`*Classify Sparseness in 2x2 Tables using Risk Ratio*

Description

Classifies sparseness in 2x2 categorical tables where one or more cells are zero. The classification uses widely applied summary measures and a continuity correction to determine whether a table exhibits mild, moderate, or severe sparseness.

Usage

```
nose.rr(nos, cc)
```

Arguments

<code>nos</code>	A numeric matrix or data.frame with 4 columns representing counts in a 2x2 table: a (top-left), b (top-right), c (bottom-left), d (bottom-right). Each row corresponds to a separate 2x2 table.
<code>cc</code>	Continuity correction factor (numeric, e.g., 0.3)

Value

A matrix combining the input counts with an extra column indicating the sparseness classification for each table.

Examples

```
# Simple example: one 2x2 table with a zero cell
xx <- matrix(c(0, 3, 2, 5), nrow = 1, byrow = TRUE)
nose.rr(xx, cc = 0.3)

# Multiple tables example: each row is a separate 2x2 table
tables <- matrix(c(
  0, 3, 2, 5,
  2, 0, 1, 4,
  0, 0, 2, 3
), nrow = 3, byrow = TRUE)
nose.rr(tables, cc = 0.3)
```

Index

nose.or, 2
nose.rd, 3
nose.rr, 4